

S#	MODE OF OPT.	ON	OFF
S10	30/50A	30A	50A
S9	1 OR 2 PUMPS	1 PUMP	2 PUMPS
S8	DEG.C/ F	C	F
S7	PUMP2 1SPD/2SPD	50HZ	2SPD
S6	50/60HZ	50HZ	60HZ
S5	PUMP1 1SPD/2SPD	1SPD	2SPD
S4	AUX. FREEZE	MUST BE OFF	
S3	CIRC/NONGIRC	CIRC	NONGIRC
S2	F.O. /SPA LITE	F.O.	SLITE
S1	TEST MODE	ON	OFF

P/N 52319HC2  
MODEL 2000M7



BALBOA INSTRUMENTS INC.  
TUSTIN, CA.

Certified to comply with the limits for a class B computing device pursuant to subpart J of part 15 of the FCC rules



60 HZ

MODEL: DUM-2000M7-DCAH

PAT. NO. 4618797

Neutral WHITE	Hot BLACK	Hot RED
USE COPPER CONDUCTOR ONLY #6 AWG MIN. WIRE = 60/75°C	EMPLOYER UNIQUEMENT DES CONDUCTEURS DE CUIVRE.	TORQUE RANGE FOR TBT: 21-23 IN. LBS

